

## Dial Test Indicators

**K 49 AD ■ K 50 AD ■ K 51 AD**  
**K 58 ■ K 59 ■ K 60**

Technical features:	K 49 / 50 / 51 AD:	K 58 / 59 / 60
Reading	0,001 mm	0,001 mm
Range	0,2 mm	0,2 mm
Dial reading	0 – 100 – 0	0 – 100 – 0
Bezel-dia.	40 mm	58 mm
Form to DIN 2270	A / B / C	A / B / C
Dimensions and accuracy	analog DIN 2270	analog DIN 2270
Length of contact point	12,8 mm	12,8 mm
Swivelling range of contact point	240°	240°
Scale cover water-protected	yes	no

K 49 AD



## Dial Gauges **M 2/25 T ■ M 2/25 S shockproof**

Reading	0,01 mm
Range	25 mm
Range per revolution	1 mm
Bezel-dia.	58 mm
Stem-dia.	8 h 6
Rack-dia.	5 h 6
Accuracy according to	DIN EN ISO 463 / Works standard 1.0200.9.0014
Measuring force minimum	0,8 N



## Contact points **573/40 ■ 573/41 ■ 573/42 R**

573/40	573/41	573/42 R
Ø 7,8 mm, L = 1,0 mm	Ø 15 mm, L = 1,5 mm	Ruby ball Ø 1 mm
Ø 7,8 mm, L = 1,5 mm	Ø 15 mm, L = 2,0 mm	Ruby ball Ø 2 mm
Ø 7,8 mm, L = 2,0 mm	Ø 20 mm, L = 1,5 mm	Ruby ball Ø 3 mm
Ø 10 mm, L = 1,0 mm	Ø 20 mm, L = 2,0 mm	Ruby ball Ø 4 mm
Ø 10 mm, L = 1,5 mm		
Ø 10 mm, L = 2,0 mm		

